

MORE FEATURES. MORE RELIABLE. MORE AFFORDABLE.

DELV-12GSDI-15

Aspect Ratio:	16:9
Brightness:	330cd/m ²
Contrast:	1000:1
Resolution:	3840x2160, 4K
Viewing Angle:	176°/176°(H/V)
Size/Type:	15.6in LCD IPS
Dimensions:	15.3x10.5x1.5 in/20.6x12x6.7 in w case
More info click here:	DELV-12GSDI-15

Items Included:

Collapsible Sunshade, Carrying Case, 15V 4-Pin XLR Power Cable, Battery Plate Bracket, V-mount, TALLY Connector Kit



12G-SDI Quad View IPS 6RU Rack Mount Monitor

The Delvcam DELV-12GSDI15 4K HDMI 12G-SDI 6RU rack mountable broadcast monitor features a 15.6-inch screen with multiple viewing options, including built-in quad and multiview, as well as a high contrast display for the ultimate cinematic experience. With multiple interfaces including 12G-SDI, 3G-SDI, and HDMI this monitor is ideal for ENG news crews, TV stations, production studios, and directors in live and post production applications.

The monitor is mounted in a removable reinforced case that features a hinged, lockable door for access to the back of the monitor and fits into a standard 19" 6RU equipment rack without the case.

Specifications

Special Functions:	<ul style="list-style-type: none"> • Quad View, Tally Interface, User Definable Function Buttons • Picture: Brightness, Contrast, Saturation, Hue, Sharpness, Temperature, Backlight • Marker: Center, Safety, Aspect • Function: Aspect, Underscan, Pixel to Pixel, Check Field, Freeze Input, Peaking, False Color • Audio: Volume, Audio Level Meter (SDI ONLY) • System: Menu Time, OSD H/V Position, OSD Rotate, Transparency, Border Width, Border Color
---------------------------	--

Input:	12G-SDI, 3G-SDI, HDMI 4K 60Hz, HDMI 1.4 4K 30Hz	Weight:	7.5 lb/26.5 lb with case
Output:	12G-SDI, 3G-SDI	Battery Plate:	N/A
Audio:	1 Speaker, Earphone Jack, Audio Level Meter (SDI only)	Power :	34W
Mount:	Rackmount	Input Current:	2.8A
		Input Voltage:	12-24VDC (XLR)

Formats/Rates

SEE MANUAL FOR COMPLETE INFORMATION SDI-SDI: 525i, 625i, HD-SDI: 1280×720 (23.98/24/25/29.97/30/50/59.94/60p), 1920×1080 /2048×1080 (50/59.94/60i) (23.98/29.97/24/25/30p)(23.98/29.97/24/25/30Psf), HD-SDI Quad Link/3G-SDI Dual Link 2SI/3G-SDI Dual Link Sq Div: 3840×2160/4096×2160 (23.98/24/25/29.97/30p)

3G-SDI: 1920×1080/2048×1080 (47.95/48/50/59.94/60p), 1920×1080/2048×1080 (50/59.94/60i) (23.98/24/25/29.97/30p)(23.98/24/25/29.97/30Psf), 1280×720 (23.98/24/25/29.97/30/50/59.94/60p) , 1920×1080/2048×1080 (50/59.94/60i) (23.98/24/25/29.97/30p)(23.98/24/25/29.97/30Psf), 1280×720 (23.98/24/25/29.97/30P)

6G-SDI Single Link: 3840×2160/4096×2160 (23.98/24/25/29.97/30p), 1920×1080/2048×1080 (47.95/48/50/59.94/60p), 3840×2160/4096×2160 (47.95/48/50/59.94/60p) 12G-SDI Single Link/3G-SDI Quad Link Sq Div/2SI: 3840×2160/4096×2160 (47.95/48/50/59.94/60p), 3840×2160/4096×2160 (23.98/24/25/29.97/30p)