

MORE FEATURES. MORE RELIABLE. MORE AFFORDABLE.

DELV-4KSDI15

More info click here: [DELV-4KSDI15](#)



- Aspect Ratio:** 16:9
Brightness: 330cd/m²
Contrast: 1000:1
Resolution: 3840x2160, 4K
Viewing Angle: 176°/176°(H/V)
Size/Type: 15in LCD, LED backlight
Dimensions: 15.3x10.5x1.5 in/20.6x12x6.7 in
w case

Items Included:

Sunshade, Carrying Case, 15V 4-Pin XLR Power Adapter, Tally Connector Kit, Battery Plate Bracket, V-Mount w/Power Cable, Rack sold separately

4K Ultra-HD Monitor with a 15" Screen

The Delvcam DELV-4KSDI15 4K UHD LCD 6RU rack mountable broadcast monitor features a 15-inch screen with multiple viewing options, including built-in quad and multiview, as well as a high contrast display for the ultimate cinematic experience. The high contrast display creates rich colors and sharp, detailed images. The monitor is mounted in a removable reinforced case and also fits into a standard 19" 6RU equipment rack without the case.

With multiple interfaces including 3G-SDI, HDMI, VGA, DVI and audio, this monitor is ideal for ENG news crews, TV stations, production studios, and directors in live and post production applications.

Specifications

Special Functions:	Split Screen, Quad View, User Adjustable Markers, Tally Interface, Check Field, Image Flip, Overscan, Underscan, Image Freeze, Color Temperature		
Input:	3G-SDI, HDMI 2.0 (4K), 3 HDMI 1080P, DVI, VGA		
Output:	3G-SDI	Battery Plate:	N/A
Audio:	1 Speaker, Earphone Jack	Power Consumption:	15W
Mount:	100x100 & 75x75 VESA Mount	Input Current:	1A
Weight:	7.5 lb/26.5 lb with case	Input Voltage:	12-24VDC (XLR)

Formats/Rates

HDMI: 4K, 1080p, 1080i, 1035i, 720p, 576p, 576i, 480p, 486i, SDI: SMPTE-125M - 480i(59.94), 1080i(60/59.94/5, 1080p (30/29/97/25/24/24sF/23.98/23.98sF)

SDI: SMPTE-292M-1080p(30/29/97/25/24/24sF/23.98/23.98sF), SMPTE-296M-720p (60/59.94/50/30/29/25/24/23.9)

SDI: SMPTE-372M-720p (60/59.94/5), 1080i(29.97/25/24/23.98), 1080p(60/59.94/50/30/29/25/24/23.98), SMPTE-425M-AB-1080p(60/59./50), Level A & Level B-720p(60/59.94/50/30/29/25/24/23.98), Level B 2x-1080i(60/59.94/5), ITU-R BT.656-576i(50)